

Laminators Approved Materials

Effective June 19, 2015

- **Silicone Caulk**

The following caulks have been tested and meet requirements:

- Pecora 860, 890, 895, 896
 - o Color-matched Pecora 890NST — Available from Laminators Inc.*
- Dow Corning® 756, 790, 791, 795, 983, 995
- GE SilGlaze® II, SilPruf®
- Novaflex® Metal Roof Sealant — Available from Laminators Inc.*

***Note:** Minimum order quantities required for certain color-matched caulks.

- **Panel Adhesive**

The following adhesives have been tested and meet requirements:

- Chem Link™ WallSecure™ High Performance Wall & Block Adhesive (VOC-compliant) — Available from Laminators Inc.
- Pecora 896

- **Fasteners**

Please contact Laminators Inc. Technical Support at 800.523.2347 for information on approved installation fasteners.

- **Air and Water Barrier[‡]**

The following air and water barriers have been tested and meet compatibility requirements for 1-Piece Tight-Fit Molding, 2-Piece Snap-Fit Molding, and Clip & Caulk installation systems:

- Henry® Air-Bloc® 31MR Fluid Applied, Vapor Permeable Elastomeric Membrane*

***Note:** All NFPA 285 and Miami-Dade compliant assemblies have been tested with Henry Air-Bloc 31MR.

[‡] *If an air and water barrier product that is not listed above is specified:*

- *Install 4" x 4" cold-formed strapping squares (20 ga. min) at each adhesive location fastened to structure using (3) #8 fasteners, or*
- *Contact Laminators Inc. Technical Support at 800.523.2347 for information on available project-specific testing for alternative liquid-applied air and water barriers.*

This document replaces any previous version published by Laminators Incorporated.

Trademarks are registered by the companies listed.